



RF COAXIAL CONNECTOR SERIES



M4



M6



P2

Features of RF Coaxial Connectors

- Meet EIA & MIL-STD standards
- Reflow process compatible
- Compliance with CE & FCC & MSDS & RoHS requirements
- Capacity 15 million pcs per month for RF Connectors
- Capacity 5 million pcs per month for RF Connectors with Switch
- Customizable specification

Ratings

- Voltage:
 - M4 & M6: 60V AC
 - P2: 250V AC
- Nominal characteristic impedance: 50Ω
- Frequency: 0~6 GHz DC
- VSWR:
 - M4 & M6: Plug 1.3 max. at 0.1~3 GHz; 1.5 max. at 3~6 GHz
Receptacle 1.3 max. at 0.1~3 GHz; 1.4 max. at 3~6 GHz
 - P2: 1.2 max. under 3 GHz; 1.3 max. at 3~6 GHz
- Operation Temperature:
 - M4 & M6: -40~+90°C
 - P2: -40~+105°C

Product No.	PCB Mounting	Operation Direction	Dimension	Pad	Switch
M4	SMT	Vertical	3.0x3.1x1.25(H)mm	3&4	w/o Switch
M6			2.0*2.0*0.60(H)mm	4	
P2			3.0*3.0*1.75(H)mm	6	w/ Switch

